

Solis-(125-255)K-EHV-5G-US-PLUS

Solis Three Phase Grid-Tied Inverters

Efficient

- 9/12 MPPTs, max. efficiency 99.0% (CEC efficiency 98.3%)
- > 1.5 DC/AC ratio
- High power tracking density 72MPPT/MW
- Compatible with 550W+ bifacial modules

Safe

- Type 4X, C5 Anti-Corrosion Level
- External signal control function
- Integrated nighttime PID recovery for optimal module performance
- Fuse free design, safe and maintenance free
- AFCI protection, proactively reduces fire risk
- High quality components from globally recognized suppliers

Smart

- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation⁽¹⁾

Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector
- Reserve DC energy storage access

Models:

Solis-125K-EHV-5G-US-PLUS
Solis-185K-EHV-5G-US-PLUS
Solis-255K-EHV-5G-US-PLUS



(1) Requires the user to use Solis monitoring

DATASHEET

Solis-(125-255)K-EHV-5G-US-PLUS

Models	125K-PLUS	185K-PLUS	255K-PLUS		
Input DC					
Max. input voltage		1500 V			
Rated voltage		950 V	1080 V		
Start-up voltage		500 V			
MPPT voltage range		480 - 1500 V			
Max. input current	9 × 30 A		12 × 30 A		
Max. short circuit current	9 × 50 A		12 × 50 A		
MPPT number / Max. input strings number	9 / 18		12 / 24		
Output AC					
Rated output power	125 kW	185 kW	255 kW		
Max. apparent output power	137.5 kVA	185 kVA	255 kVA		
Max. output power	137.5 kW	185 kW	255 kW		
Rated grid voltage		3Φ/PE, 600 V	3Φ/PE, 800 V		
Rated grid frequency		60 Hz			
Max. output current	132.3 A	178.0 A	184.0 A		
Power factor		> 0.99 (0.8 leading - 0.8 lagging)			
THDi		< 3%			
Efficiency					
Max. efficiency	98.6%	98.7%	99.0%		
CEC efficiency		98.3%			
Protection					
DC reverse-polarity protection		Yes			
Surge protection		DC Type II / AC Type II			
Ground fault monitoring		Yes			
Anti-islanding protection		Yes			
Strings monitoring		Yes			
Integrated AFCI		Yes			
Integrated PID recovery		Yes			
I/V Curve scanning		Yes			
General Data					
Dimensions (W × H × D)		46.1 × 30.3 × 15.1 in (1170 × 770 × 384 mm)			
Weight	240 lbs (109 kgs)	249.0 lbs (113 kgs)			
Topology		Transformerless			
Self-consumption (night)		< 2 W			
Relative humidity		0 - 100%			
Operating ambient temperature range		-22°F to 140°F (-30°C to 60°C)			
Storage environment		-40°F to 176°F (-40°C to 80°C)			
Ingress protection		TYPE 4X			
Cooling concept		Intelligent fan-cooling			
Max. operation altitude		13,120 ft (4000 m)			
Compliance	UL 1741SB, UL 1998, UL1699B, IEEE 1547-2018, FCC Part 15 (Class A & B), CAN/CSA C22.2 107.1-1, California Rule 21				
Features					
DC connection		MC4 connector			
AC connection		OT terminal (750 MCM)			
Display		LCD			
Communication		RS485, Optional: PLC			